



GA Series

Torque range • Auto-shut off • $\text{C}\epsilon$ • XS-38D Controller 

0,08 to 1,18 NM



- designed for operator comfort : light weight and small sized, full ergonomic design
- designed for productivity : Accurate shut-off clutch (+/- 3%), speed control, maintenance free (shut-off operated by magnetic sensor - no wearing)
- designed for quality : ESD free, External torque adjustment scale, soft start, double hit mode.
- Noise level : <70 dBA, vibration level : <2,5 m/s²

GA Series

Model	Torque range (Nm)	Rotation speed (rpm)	Drive	Starting system	Weight (Kg)	Code
GA 150 ESD	0,08 - 0,78	700 or 1000	Hex 1/4"	Lever	0,31	6-1040011
GA 180 ESD	0,1 - 1,18	450 or 700	Hex 1/4"	Lever	0,31	6-1040012
GA 150 P ESD	0,08 - 0,78	700 or 1000	Hex 1/4"	Push to start	0,31	6-1040013
GA 180 P ESD	0,1 - 1,18	450 or 700	Hex 1/4"	Push to start	0,31	6-1040014

Standard equipment (supplied with the tool)

- Power supply cable 3 m
- 2 carbon brushes
- 2 bits Philips n° 0, n° 1
- Clutch adjustment springs
- Suspension ring
- User manual

Accessories & Wear spare parts

							
Designation	Carbon brush	Brush cap	Torque ring cover	Ring for arm mounting	Extra long cable 5 m	Spiral cable 3,5 m	Screw vacuum Pick-up
Code	6-1041219	6-1041203	6-1041212	6-1041500	6-1044703	6-1010413	6-1052500

Vacuum pick up assembly is provided without the sleeve (on request). The recommended bit length is 44 mm long. Feeting size : diameter 4 mm.